

# Safety data sheet

## According to 1907/2006 EEC Article 31

Printing date: 16.04.2014







Version: 15

Revision: 16.04.2014

### 1 Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** **TWIN AIR MP CONTACT CLEAN 500 ml**
- **Article number:** 11-00000-1817
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Sector of Use**  
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)  
SU21 Consumer uses: Private households / general public / consumers
- **Product category** PC35 Washing and cleaning products (including solvent based products)
- **Process category** PROC11 Non industrial spraying
- **Application of the substance / the mixture** Cleaner solvent
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Mobacc/Pharmaspray/Eurofill  
9640 AH Veendam  
The Netherlands  
Tel: +31(0)598 626666  
Fax: +31(0)598 625976  
E-mail: j.sleumer@mobacc.com
- **Further information obtainable from:** Research & Development/E-mail: j.sleumer@mobacc.com
- **1.4 Emergency telephone number:** During normal opening hours: Tel: +31(0)598 626666

### 2 Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
-  GHS02 flame  
 Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
-  GHS08 health hazard  
 Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.
-  GHS09 environment  
 Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.
-  GHS07  
 Eye Irrit. 2 H319 Causes serious eye irritation.  
 STOT SE 3 H336 May cause drowsiness or dizziness.
- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**
-  Xi; Irritant  
 R36: Irritating to eyes.
-  F+; Extremely flammable  
 R12: Extremely flammable.

(Contd. on page 2)

# Safety data sheet

## According to 1907/2006 EEC Article 31

Printing date: 16.04.2014

Version: 15

Revision: 16.04.2014

**Trade name: TWIN AIR MP CONTACT CLEAN 500 ml**

(Contd. of page 1)



N; Dangerous for the environment

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R66-67: Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

**Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

Warning! Pressurized container.

Has a narcotizing effect.

**Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

**2.2 Label elements**
**Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

**Hazard pictograms**


GHS02 GHS07 GHS08 GHS09

**Signal word Danger**
**Hazard-determining components of labelling:**

Naphtha (petroleum), hydrotreated light

Pentane

propan-2-ol

**Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

H411 Toxic to aquatic life with long lasting effects.

**Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P251 Pressurized container: Do not pierce or burn, even after use.

P211 Do not spray on an open flame or other ignition source.

P273 Avoid release to the environment.

P271 Use only outdoors or in a well-ventilated area.

P261 Avoid breathing mist/vapours/spray.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P331 Do NOT induce vomiting.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P403 Store in a well-ventilated place.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.

(Contd. on page 3)

# Safety data sheet

## According to 1907/2006 EEC Article 31

Printing date: 16.04.2014

Version: 15

Revision: 16.04.2014

**Trade name: TWIN AIR MP CONTACT CLEAN 500 ml**

(Contd. of page 2)

- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### 3 Composition/information on ingredients

#### 3.1 Substances

##### Additional information:

CAS: 64742-49-0 EC number: 920-750-0 Reg.nr.: 01-2119473851-33	Naphtha (petroleum), hydrotreated light Xn R65; F R11; N R51/53 R66-67 Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336	25-<50%
CAS: 67-63-0 EINECS: 200-661-7 Reg.nr.: 01-2119457558-25	propan-2-ol Xi R36; F R11 R67 Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	25-<50%
CAS: 109-66-0 EINECS: 203-692-4 Reg.nr.: 01-2119459286-30	Pentane Xn R65; F+ R12; N R51/53 R66-67 Flam. Liq. 1, H224; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336	10-<25%
CAS: 124-38-9 EINECS: 204-696-9	carbon dioxide Press. Gas, H280	3-<10%

- **3.2 Mixtures**
- **Description:** Active substance with propellant
- **Dangerous components:** -

##### Ingredients according to detergents guideline 648/2004/EC

aliphatic hydrocarbons	≥ 30%
------------------------	-------

##### Additional information:

### 4 First aid measures

- **4.1 Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Do not induce vomiting; call for medical help immediately.
- **4.2 Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### 5 Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**  
Water haze  
Fire-extinguishing powder  
Carbon dioxide  
Alcohol resistant foam

(Contd. on page 4)

# Safety data sheet

## According to 1907/2006 EEC Article 31

Printing date: 16.04.2014

Version: 15

Revision: 16.04.2014

**Trade name: TWIN AIR MP CONTACT CLEAN 500 ml**

(Contd. of page 3)

- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** Mount respiratory protective device.

### 6 Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### 7 Handling and storage

- **7.1 Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.
- **Information about fire - and explosion protection:**  
Do not spray onto a naked flame or any incandescent material.  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Store in a cool location.  
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:**  
Observe official regulations on storing packagings with pressurized containers.
- **Further information about storage conditions:**  
Keep receptacle tightly sealed.  
Do not seal receptacle gas tight.  
Store in cool, dry conditions in well sealed receptacles.  
Protect from heat and direct sunlight.
- **7.3 Specific end use(s)** No further relevant information available.

### 8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**

#### Ingredients with limit values that require monitoring at the workplace:

##### 67-63-0 propan-2-ol

WEL	Short-term value: 1250 mg/m <sup>3</sup> , 500 ppm Long-term value: 999 mg/m <sup>3</sup> , 400 ppm
-----	--

(Contd. on page 5)

# Safety data sheet

## According to 1907/2006 EEC Article 31

Printing date: 16.04.2014

Version: 15

Revision: 16.04.2014

**Trade name: TWIN AIR MP CONTACT CLEAN 500 ml**

(Contd. of page 4)

**109-66-0 Pentane**WEL Long-term value: 1800 mg/m<sup>3</sup>, 600 ppm**124-38-9 carbon dioxide**WEL Short-term value: 27400 mg/m<sup>3</sup>, 15000 ppm  
Long-term value: 9150 mg/m<sup>3</sup>, 5000 ppm· **DNELs****64742-49-0 Naphtha (petroleum), hydrotreated light**

Oral	DNEL Long term-systemic	699 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	699 mg/kg bw/day (Consumer) 773 mg/kg bw/day (Worker)
Inhalative	DNEL Long term-systemic	608 mg/m <sup>3</sup> (Consumer) 2035 mg/m <sup>3</sup> (Worker)

**67-63-0 propan-2-ol**

Oral	DNEL Long term-systemic	26 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	319 mg/kg bw/day (Consumer) 888 mg/kg bw/day (Worker)
Inhalative	DNEL Long term-systemic	89 mg/m <sup>3</sup> (Consumer) 500 mg/m <sup>3</sup> (Worker)

**109-66-0 Pentane**

Oral	DNEL Long term-systemic	214 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	214 mg/kg bw/day (Consumer) 432 mg/kg bw/day (Worker)
Inhalative	DNEL Long term-systemic	643 mg/m <sup>3</sup> (Consumer) 3000 mg/m <sup>3</sup> (Worker)

· **Additional information:** The lists valid during the making were used as basis.· **8.2 Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Do not inhale gases / fumes / aerosols.
- Avoid contact with the eyes.
- Avoid contact with the eyes and skin.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter AX/P2

· **Protection of hands:**

Protective gloves

Solvent resistant gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves** Nitrile rubber, NBR· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

# Safety data sheet

## According to 1907/2006 EEC Article 31

Printing date: 16.04.2014

Version: 15

Revision: 16.04.2014

Trade name: TWIN AIR MP CONTACT CLEAN 500 ml

(Contd. of page 5)

## · Eye protection:



Tightly sealed goggles

## · Body protection: Use protective suit.

### 9 Physical and chemical properties

## · 9.1 Information on basic physical and chemical properties

## · General Information

## · Appearance:

Form:	Aerosol
Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.

· pH-value: Not determined.

## · Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	36 °C

· Flash point: -35 °C

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: 200 °C

· Decomposition temperature: Not determined.

· Self-igniting: Product is not selfigniting.

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

## · Explosion limits:

Lower:	0.7 Vol %
Upper:	12.0 Vol %

· Vapour pressure at 20 °C: 573 hPa

· Density at 20 °C: 0.762 g/cm<sup>3</sup>

· Relative density: Not determined.

· Vapour density: Not determined.

· Evaporation rate: Not applicable.

## · Solubility in / Miscibility with water:

Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

## · Viscosity:

Dynamic:	Not determined.
Kinematic:	Not determined.

## · Solvent content:

Organic solvents: 96.0 %

· 9.2 Other information: No further relevant information available.

GB

(Contd. on page 7)

# Safety data sheet

## According to 1907/2006 EEC Article 31

Printing date: 16.04.2014

Version: 15

Revision: 16.04.2014

**Trade name: TWIN AIR MP CONTACT CLEAN 500 ml**

(Contd. of page 6)

### 10 Stability and reactivity

- **10.1 Reactivity**
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### 11 Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values relevant for classification:**

**64742-49-0 Naphtha (petroleum), hydrotreated light**

Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>2800 mg/kg (rabbit)
Inhalative	LC50/4 h	>23 mg/l (rat)

**67-63-0 propan-2-ol**

Oral	LD50	5840 mg/kg (rat)
Dermal	LD50	13900 mg/kg (rabbit)
Inhalative	LC50/6h	25000 mg/m <sup>3</sup> (rat)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**  
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:  
Irritant

### 12 Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:**

**64742-49-0 Naphtha (petroleum), hydrotreated light**

EC50/48h	3 mg/l (Daphnia magna)
EL50 (72h)	10-30 mg/l (Pseudokirchneriella subcapitata)
LL50 (96h)	>13.4 mg/l (Oncorhynchus mykiss (96h))
LOEC (21 days)	0.32 mg/l (Daphnia magna)
NOEC (21 days)	0.17 mg/l (Daphnia magna)
NOELR (72h)	10 mg/l (Pseudokirchneriella subcapitata)

**67-63-0 propan-2-ol**

LC50 (24h)	9714 mg/l (Daphnia magna)
LC50/96h	9640 mg/l (Pimephales promelas)
LOEC (8 days)	1000 mg/l (algae)

**109-66-0 Pentane**

EC50 (72h)	10.7 mg/l (Pseudokirchneriella subcapitata)
------------	---

(Contd. on page 8)

# Safety data sheet

## According to 1907/2006 EEC Article 31

Printing date: 16.04.2014

Version: 15

Revision: 16.04.2014

**Trade name: TWIN AIR MP CONTACT CLEAN 500 ml**

(Contd. of page 7)



EC50/48h	2.7 mg/l (Daphnia magna)
LC50/96h	4.26 mg/l (Oncorhynchus mykiss (96h))
NOEC (72h)	7.51 mg/l (Pseudokirchneriella subcapitata)

- **12.2 Persistence and degradability** Easily biodegradable
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.  
Also poisonous for fish and plankton in water bodies.  
Toxic for aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

### 13 Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

- **14.1 UN-Number**
  - **ADR, IMDG, IATA** UN1950
  - **14.2 UN proper shipping name**
  - **ADR** 1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS
  - **IMDG** AEROSOLS (Naphtha (petroleum), hydrotreated light, PENTANES), MARINE POLLUTANT
  - **IATA** AEROSOLS, flammable
  - **14.3 Transport hazard class(es)**
  - **ADR**
- 

- **Class** 2 5F Gases.
  - **Label** 2.1

(Contd. on page 9)

GB

# Safety data sheet

## According to 1907/2006 EEC Article 31

Printing date: 16.04.2014

Version: 15

Revision: 16.04.2014

Trade name: TWIN AIR MP CONTACT CLEAN 500 ml

(Contd. of page 8)

· **IMDG**

· **Class** 2.1  
 · **Label** 2.1

· **IATA**

· **Class** 2.1  
 · **Label** 2.1

· **14.4 Packing group**  
 · **ADR, IMDG, IATA** Void

· **14.5 Environmental hazards:** Product contains environmentally hazardous substances:  
 Naphtha (petroleum), hydrotreated light  
 · **Marine pollutant:** Yes  
 Symbol (fish and tree)  
 · **Special marking (ADR):** Symbol (fish and tree)

· **14.6 Special precautions for user** Warning: Gases.  
 · **Danger code (Kemler):** -  
 · **EMS Number:** F-D,S-U

· **14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

· **Transport/Additional information:**

· **ADR**  
 · **Limited quantities (LQ)** 1L  
 · **Transport category** 2  
 · **Tunnel restriction code** D

· **UN "Model Regulation":** UN1950, AEROSOLS, ENVIRONMENTALLY HAZARDOUS, 2.1

### 15 Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**· **National regulations:**· **Technical instructions (air):**

Class	Share in %
NK	75-<100

· **VOC-CH** 96.00 %  
 · **VOC-EU** 731.5 g/l  
 · **Danish MAL Code** 5-3

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

GB

(Contd. on page 10)

# Safety data sheet

## According to 1907/2006 EEC Article 31

Printing date: 16.04.2014

Version: 15

Revision: 16.04.2014

**Trade name: TWIN AIR MP CONTACT CLEAN 500 ml**

(Contd. of page 9)

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H224 Extremely flammable liquid and vapour.
- H225 Highly flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.
  
- R11 Highly flammable.
- R12 Extremely flammable.
- R36 Irritating to eyes.
- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R65 Harmful: may cause lung damage if swallowed.
- R66 Repeated exposure may cause skin dryness or cracking.
- R67 Vapours may cause drowsiness and dizziness.

· **Department issuing MSDS:** Research & Development

· **Contact:** Ing. J. Sleumer

· **Abbreviations and acronyms:**

- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- ICAO: International Civil Aviation Organization
- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonized System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- MAL-Code: Måleteknisk Arbejdshygiejnisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark)
- DNEL: Derived No-Effect Level (REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- Flam. Aerosol 1: Flammable aerosols, Hazard Category 1
- Press. Gas: Gases under pressure: Liquefied gas
- Flam. Liq. 1: Flammable liquids, Hazard Category 1
- Flam. Liq. 2: Flammable liquids, Hazard Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2
- STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
- Asp. Tox. 1: Aspiration hazard, Hazard Category 1
- Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

· **\* Data compared to the previous version altered. \***

GB